State of Tennessee Department of Environment and Conservation Division of Air Pollution Control William R. Snodgrass Tennessee Tower 312 Rosa L. Parks Avenue, 15th Floor Nashville, TN 37243 Telephone: (615) 532-0554



NON-TITLE V PERMIT APPLICATION FACILITY IDENTIFICATION

Please	e type or print and submit in			ttach appropriat	e source description forms.		
		SITI	E INFORMATION				
1. Organization's legal nar				For	APC Company point no.		
Volunteer Community Hospital				APC use			
2. Site name (if different from legal name)					APC Log/Permit no.		
3. Site address (St./Rd./Hwy.)					County name		
161 Mt. Pelia rd. Tenn.							
City or distance to nearest Martin	town		Zip code 38237	4. NA 62199	ICS or SIC code		
5. Site location (in lat. /long.)	Latitude 36 20'1N	:11		Longitud 88 52'1'			
	CONTAC	T INFORM	ATION (RESPONS	IBLE PERS	ON)		
6. Responsible person/Aut) Roger Hill					mber with area code		
Mailing address (St./Rd./ 161 Mt. Pelia Rd.	Hwy.)		÷ 1	Fax number with area code 731-588-3469			
City Martin		State TN	Zip code 38237	Email ad	dress ill@chs.net		
	CON	NTACT INF	ORMATION (TEC	HNICAL)			
7. Principal technical conta			· · · · · · · · · · · · · · · · · · ·		mber with area code		
Roger Hill				731-588-3465			
Mailing address (St./Rd./	Hwy.)			Fax number with area code			
161 Mt. Pelia Rd.				731-588-3469			
City		State	Zip code				
Martin		Tn.	38237	roger_h	ill@chs.net		
	C	ONTACT IN	NFORMATION (BI	LLING)			
8. Billing contact Roger Hill				731-588	mber with area code -3465		
Mailing address (St./Rd./ 161 Mt. Pelia Rd.	Hwy.)			Fax number with area code 731-588-3469			
City		State	Zip code	Email address			
Martin		Tn.	38237	roger_hi	ill@chs.net		
	E	MISSION S	OURCE INFORMA	ATION			
9. Emission source no. (nun	nber which uniquely identifie	es this source)					
10. Brief description of emis	sion source						
Diesel fired emergency ge	nerator						
11. Normal operation:	Hours/Day	Days/W	Veek	Weeks/Year	Days/Year		
12. Percent annual throughput	Dec. – Feb.	March -	– May	June – Augu	st Sept. – Nov.		

	TYPE OF PI	ERMIT REQUESTED		
13. Operating permit Date construct		Date completed	Last permit no.	Emission source referen
(X)			350	number
Construction permit Last permit no).		Emission source	reference number
()				
If you choose Construction permit, then choose ei	ith on Navy Construction	n Modification or Location to	nefer	
New Construction permit, their choose er		tarting date	Completion	date
New Constitution	101	turting date	Completion	
()				
Modification	D	Date modification started or wil	l start Date comple	eted or will complete
Location transf	fer T	ransfer date	Address of l	ast location
()				
14. Describe changes that have been made to this ed	quinment or operation	on since the last construction	or operating permit	annlication:
14. Describe changes that have been made to this en	quipment or operation	on since the last constituction	or operating permit	application.
Construction complete				
		GNATURE		
Based upon information and belief formed after a	reasonable inquiry	, I, as the responsible perso	n of the above ment	ioned facility, certify that the
information contained in this application and any	attached application	n(s) is accurate and true to	the best of my know	ledge. As specified in TCA
Section 39-16-702(a)(4), this declaration is made	under penalty of pe	erjury.		
15. Signature (application must be signed before it w	rill be processed)		Date	
(Kapp 41 11)			4-10-1	15
Moy Dill				
Signer's name (type of print)	Title		Phone number with a	
Roger Hill	PLONT	Dir	731- 388	-3465
0				
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95%	d electrostatic precipita And Low: I	Less than 80%.	respond to the following	ng percentages:
Note: For cyclones, settling chambers, wet scrubbers, and	d electrostatic precipita And Low: I ipment, indicate the se	ators; the efficiency ranges cor Less than 80%. equence. For example: 008'010	respond to the following	ng percentages:
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other	d electrostatic precipite And Low: I ipment, indicate the se and specify in the con	ators; the efficiency ranges cor Less than 80%. equence. For example: 008'010 mments.	respond to the following 1.97%	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipite And Low: I ipment, indicate the se and specify in the con000	ators; the efficiency ranges cor Less than 80%. equence. For example: 008'010 mments.	respond to the following 1.97%	041
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other	d electrostatic precipitation And Low: I ipment, indicate the ser and specify in the continuous con	ators; the efficiency ranges cor Less than 80%. Equence. For example: 008'010 mments. Limestone Injection – Limestone Injection – Liquid Filtration Syste	respond to the following 197% Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipits And Low: I ipment, indicate the se and specify in the con	ators; the efficiency ranges cor Less than 80%. Equence. For example: 008'010 mments. Limestone Injection – Limestone Injection – Liquid Filtration Syste Mist Eliminator – Higl	prespond to the following property prop	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipitation And Low: I ipment, indicate the ser and specify in the constant of the constant	ators; the efficiency ranges cor Less than 80%. Equence. For example: 008'010 mments. Limestone Injection – Limestone Injection – Liquid Filtration Syste Mist Eliminator – Higl Mist Eliminator – Low	prespond to the following property prop	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipits And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor Less than 80%. Equence. For example: 008'010 mments. Limestone Injection – Liquid Filtration Syste Mist Eliminator – Higl Mist Eliminator – Low Process Change	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipitation And Low: I important indicate the ser and specify in the constant indicate the ser and specify in the constant indicate indicate in the constant indicate	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 mments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change	nespond to the following 197% Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipitation And Low: I And Low: I ipment, indicate the ser and specify in the constant of the ser and specify in the ser and specify in the ser and specify in the ser and specific of the serian specific of the ser and specific of t	ators; the efficiency ranges cor Less than 80%. Equence. For example: 008'010 mments. Limestone Injection – Liquid Filtration Syste Mist Eliminator – High Mist Eliminator – Low Process Change Process Gas Recovery Settling Chamber – High	prespond to the following property process of the following process of	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipitation And Low: I ipment, indicate the ser and specify in the constant of the ser and specific in the ser and speci	ators; the efficiency ranges cor Less than 80%. Equence. For example: 008'010 mments. Limestone Injection – Liquid Filtration Syste Mist Eliminator – High Mist Eliminator – Low Process Change	prespond to the following property and the following property are the following property are the following property and the following property are the follo	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipitation And Low: I ipment, indicate the ser and specify in the constant of the ser and specific in the ser and speci	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Emments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Enclosed Process Gas Recovery Settling Chamber — High Settling Chamber — Low Settling Chamber — Low	respond to the following. 97% Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment. Activated Carbon Adsorption. Afterburner – Direct Flame Materburner – Direct Flame With Heat Exchanger. Afterburner – Catalytic. Afterburner – Catalytic with Heat Exchanger. Alkalized Alumina	d electrostatic precipits And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Equence. Eq	prespond to the following property and the following property are followed by the following property and the following property are followed by the following property and the following property are followed by the following property and the following property are followed by the following property and the following property are followed by the following property and the following property are followed by the following property are followed by the following property and the following property are followed by the following property and the following property are followed by the following property and the following property are followed by the following property and the following property are followed by the following property are followed by the following property and the following property are followed by the following property and the following property are followed by the following property and the following property are followed by the followed by	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipits And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — Higl Mist Eliminator — Low Process Change Process Enclosed Process Gas Recovery Settling Chamber — Higl Settling Chamber — Might Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — Cores (Gaseous)	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment. Activated Carbon Adsorption. Afterburner – Direct Flame Materburner – Direct Flame With Heat Exchanger. Afterburner – Catalytic. Afterburner – Catalytic with Heat Exchanger. Alkalized Alumina	d electrostatic precipits And Low: I sipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Inments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Enclosed Process Gas Recovery Settling Chamber — Hi Settling Chamber — Hi Settling Chamber — Los Spray Tower (Gaseous Sulfuric Acid Plant — G	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipita And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 mments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — Hig Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — Hi Settling Chamber — Hi Settling Chamber — Mo Settling Chamber — Mo Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — C Sulfuric Acid Plant — I Sulfur Plant	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipita And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — Hig Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — Hi Settling Chamber — Hi Settling Chamber — Mi Settling Chamber — Lo Spray Tower (Gaseous Sulfuric Acid Plant — C Sulfuric Acid Plant — I Sulfur Plant Vapor Recovery Syste Other Enclosures)	prespond to the following process of the follo	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipita And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — Hig Mist Eliminator — Hog Mist Eliminator — Hog Process Change Process Gas Recovery Settling Chamber — Hig Settling Chamber — Hig Settling Chamber — Mig Settling Chamber — Log Spray Tower (Gaseous Sulfuric Acid Plant — C Sulfuric Acid Plant — Ig Sulfur Plant Vapor Recovery Syste Other Enclosures) Venturi Scrubber (Gase	prespond to the following process of the follo	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipita And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Emments. Limestone Injection — Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — High Settling Chamber — Mighting Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — C Sulfuric Acid Plant — I Sulfur Plant Vapor Recovery Syste Other Enclosures) Venturi Scrubber (Gas Wet Scrubber — High I	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipita And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — High Settling Chamber — High Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — G Sulfuric Acid Plant — I Sulfur Plant	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipits And Low: I And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — Hi Settling Chamber — Hi Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — C Sulfuric Acid Plant — I Sulfur Plant Vapor Recovery Syste Other Enclosures) Venturi Scrubber (Gas Wet Scrubber — High I Wet Scrubber — Mediu Wet Scrubber — Low E	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment. Activated Carbon Adsorption. Afterburner – Direct Flame Afterburner – Direct Flame with Heat Exchanger. Afterburner – Catalytic. Afterburner – Catalytic with Heat Exchanger. Alkalized Alumina Catalytic Oxidation – Flue Gas Desulfurization. Cyclone – High Efficiency. Cyclone – Medium Efficiency Cyclone – Low Efficiency. Dust Suppression by Chemical Stabilizers or Wetting Age Electrostatic Precipitator – High Efficiency. Electrostatic Precipitator – Low Efficiency. Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Medium Temperature Fabric Filter – Medium Temperature Fabric Filter – Metal Screens (Cotton Gins) Flaring. Gas Adsorption Column Packed	d electrostatic precipits And Low: I And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — Hi Settling Chamber — Hi Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — C Sulfuric Acid Plant — I Sulfur Plant Vapor Recovery Syste Other Enclosures) Venturi Scrubber (Gas Wet Scrubber — High I Wet Scrubber — Mediu Wet Scrubber — Low E	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipita And Low: I And Low: I ipment, indicate the se and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — Hi Settling Chamber — Hi Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — C Sulfuric Acid Plant — I Sulfur Plant Vapor Recovery Syste Other Enclosures) Venturi Scrubber (Gas Wet Scrubber — High I Wet Scrubber — Mediu Wet Scrubber — Low E	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment. Activated Carbon Adsorption. Afterburner – Direct Flame Afterburner – Direct Flame with Heat Exchanger. Afterburner – Catalytic. Afterburner – Catalytic with Heat Exchanger. Alkalized Alumina Catalytic Oxidation – Flue Gas Desulfurization. Cyclone – High Efficiency. Cyclone – Medium Efficiency Cyclone – Low Efficiency. Dust Suppression by Chemical Stabilizers or Wetting Age Electrostatic Precipitator – High Efficiency. Electrostatic Precipitator – Low Efficiency. Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Medium Temperature Fabric Filter – Metal Screens (Cotton Gins) Flaring. Gas Adsorption Column – Packed Gas Adsorption Column – Tray Type. Gas Scrubber (General: Not Classified).	d electrostatic precipits And Low: I ipment, indicate the set and specify in the constant of t	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — High Settling Chamber — High Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — Coulfuric Acid Plant — I Sulfur Plant	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment. Activated Carbon Adsorption. Afterburner – Direct Flame Afterburner – Direct Flame with Heat Exchanger. Afterburner – Catalytic. Afterburner – Catalytic with Heat Exchanger. Alkalized Alumina Catalytic Oxidation – Flue Gas Desulfurization. Cyclone – High Efficiency. Cyclone – Medium Efficiency. Cyclone – Low Efficiency. Dust Suppression by Chemical Stabilizers or Wetting Age Electrostatic Precipitator – High Efficiency. Electrostatic Precipitator – High Efficiency. Fabric Filter – High Temperature Fabric Filter – Medium Temperature Fabric Filter – Medium Temperature Fabric Filter – Metal Screens (Cotton Gins) Flaring. Gas Adsorption Column – Packed Gas Adsorption Column – Tray Type. Gas Scrubber (General: Not Classified).	d electrostatic precipits And Low: I ipment, indicate the set and specify in the constant of the set and specify in the	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — Hi Settling Chamber — Hi Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — C Sulfuric Acid Plant — I Sulfur Plant	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipits And Low: I And Low: I ipment, indicate the se and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Enclosed Process Gas Recovery Settling Chamber — High Settling Chamber — High Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — G Sulfuric Acid Plant — I Sulfur Plant Vapor Recovery Syste Other Enclosures) Venturi Scrubber — High I Wet Scrubber — High I Wet Scrubber — Low E Wet Suppression by W In Estimation Method Codes Teles of process	prespond to the following process of the follo	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipits And Low: I And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Enclosed Process Gas Recovery Settling Chamber — High Settling Chamber — High Settling Chamber — Low Spray Tower (Gaseous Sulfuric Acid Plant — Igh Sulfuric Scrubber — High Igh Wet Scrubber — High Igh Wet Scrubber — Low Egh Wet Suppression by Wet Estimation Method Codes The of process Compilation of Air Pollution Igh Control of Sulfurion Igh Sulfurion Ig	Dry	
Note: For cyclones, settling chambers, wet scrubbers, and High: 95-99+%. Medium: 80-95% If the system has several pieces of connected control equi If none of the below codes fit, use 999 as a code for other No Equipment	d electrostatic precipita And Low: I And Low: I ipment, indicate the se r and specify in the con	ators; the efficiency ranges cor- Less than 80%. Equence. For example: 008'010 Imments. Limestone Injection — Limestone Injection — Liquid Filtration Syste Mist Eliminator — High Mist Eliminator — Low Process Change Process Gas Recovery Settling Chamber — Hi Settling Chamber — Hi Settling Chamber — Los Spray Tower (Gaseous Sulfuric Acid Plant — I Sulfur Plant	Dry	